

Wright™ & Haloscale™

Respirometers

*Redefining Accuracy
Beyond the Standard*



Wright Mark 8

- For minute volume measurement with facility for measuring tidal volume
- Small inner dial records 0-1 liter
- Large outer dial records 0-100 liters
- Dial layout: separate small fractional liter and large full liter dials offset
- Connections: 22mm male BS/ISO taper, inlet and outlet
- Dial Diameter: 35mm (1.4 in)
- Overall Dimensions: 70 mm x 60 mm (2.75 in x 2.35 in)
- Weight: 130 g (4.6 oz)




Wright Mark 14

- For tidal volume measurement with facility for measuring minute volume
- Small inner dial records 0-100 liters
- Large outer dial records 0-1 liter
- Dial layout: separate small full liter large fractional liter dials offset
- Connections: 22mm male BS/ISO taper, inlet and outlet
- Dial Diameter: 35mm (1.4 in)
- Overall Dimensions: 70 mm x 60 mm (2.75 in x 2.35 in)
- Weight: 130 g (4.6 oz)



Haloscale Standard

- For both tidal volume and minute volume measurement
- Inner concentric dial records 0-1 liter
- Outer concentric dial records 0-100 liters
- Dial Layout: Dual concentric fractional and full liter dials
- Connections: 15mm female inlet/ 22mm female BS/ISO outlet
- Dial Diameter: 57 mm (2.25 in)
- Overall Dimensions: 72 mm x 70 mm (2.85 in x 2.75 in)
- Weight: 160 g (5.7 oz)



Wright-Gard Protective Cover

- Minimizes damage caused by impact
- Protects vulnerable external parts
- One piece 1/4 inch natural rubber covers entire outer body
- Allows full view of dial as well as access to on/off and reset buttons
- Special safety harness is also available
- Fits both new and old style Wright and Haloscale respirometers

Redefining Accuracy. Beyond Expectations.

No respiratory volume measurement instrument is more recognized throughout the world.

All models feature push button on/off and reset, and are supplied complete with two circuit adapters and safety harness in a fully padded carrying/storage case. An optional protective cover kit is available for added protection from inadvertent impacts while in use. All models have updated, easier to read dials.



Clinical Applications

- **Routine Checks of Mechanical Ventilation**
Respirometers are used to perform routine checks of patient's tidal volumes to guarantee accurate ventilator performance.
- **Ventilator Weaning**
When blood gas analysis indicates weaning can be attempted, respirometers make ideal instruments to determine the success of weaning by measuring tidal and minute volume levels.
- **Recovery**
Respirometers are ideal instruments to ensure the level of the patient's lung function before leaving the recovery area.
- **Anesthesia**
Placed in the expiratory circuit, respirometers are used to measure tidal and minute volumes to ensure adequate ventilation on both spontaneously breathing and mechanically ventilated patients.

Technical Specifications

Accuracy:

Tidal volumes:

± 3% for minute volumes exceeding 5 LPM

± 4% for minute volume of 4 LPM

Continuous flow:

± 2% @ 16 LPM

+ 5% to + 10% @ 60 LPM

Sensitivity:

Starts volume registration at not more than 2.5 LPM

Resistance:

Proportional to square of the flow rate and not more than 2cm H₂O @ 100 LPM

Dead Space:

22 ml

Permissible Gases:

All respirable gases

Maximum Temp:

55^o C (131^o F)

Maximum internal to external pressure:

30cm H₂O

Maximum leakage:

60ml/min at 30cm H₂O (to ASTM F1208-89)

Maximum Recommended Flow Rate:

60 LPM (300LPM continuous flow for short periods)

Sterilization:

ETO - 55^o C (131^o F) Maximum

Maintenance Program

As the original manufacturer of Wright Respirometers, we are excited to announce our enhanced services for all of our respirometer units.

One call. One price. One solution.

- Call 800.635.3200 for your reference number
- Send in your unit
- We do all repairs and factory calibration for one low price.

Sterilization

• Ethylene Oxide (ETO)

The new Wright and Haloscale respirometers are sterilized by Ethylene Oxide sterilization following the cycle recommended in the product directions for use.

• Other Sterilization Methods

No other methods of sterilization can be used. Submersion in cold disinfectants or autoclaving will severely damage the instrument and void the product warranty.

Warranty

Wright and Haloscale Respirometers are warranted for one year from date of purchase for defects in material and workmanship. Units that have been dropped, misused, or suffered damage due to repair attempts by untrained personnel are excluded.

Contact Information

Phone: 800.574.7374 303.666.5555

Email: sales@nspirehealth.com

Web: www.nspirehealth.com



©Copyright nSpire Health 2007. Due to continual innovations, nSpire Health reserves the right to change specifications without notice. Wright and Haloscale are trademarks of nSpire Health.